


(19)  **Europäisches Patentamt**
European Patent Office
Office européen des brevets



(11) **EP 0 883 084 A2**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
 09.12.1998 Bulletin 1998/50

(51) Int. Cl.⁶: G06K 19/077, G06K 7/00

(21) Application number: 98110232.0

(22) Date of filing: 04.06.1998

(84) Designated Contracting States:
 AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
 MC NL PT SE
 Designated Extension States:
 AL LT LV MK RO SI

• Kobayashi, Toshiharu
 Shinagawa-ku, Tokyo (JP)
 • Okaue, Takumi
 Shinagawa-ku, Tokyo (JP)
 • Sassa, Akira
 Shinagawa-ku, Tokyo (JP)

(30) Priority: 04.06.1997 JP 146914/97
 30.09.1997 JP 267181/97

(71) Applicant: SONY CORPORATION
 Tokyo (JP)

(74) Representative:
 Körber, Wolfhart, Dr. rer.nat. et al
 Patentanwälte
 Mitscherlich & Partner,
 Sonnenstrasse 33
 80331 München (DE)

(72) Inventors:
 • Kondo, Yoshio
 Shinagawa-ku, Tokyo (JP)

(54) **Memory card, and receptacle for same**

(57) A memory card is disclosed which has a card body (2) having a concavity (9) formed at the forward end thereof in the inserting direction and in which terminals (5) are disposed and projections (10) are formed between the terminals (5) to prevent the terminals (5) from being touched or accessed from outside. A receptacle for the memory card is also disclosed. The memory card has a simple structure designed to positively protect the terminals and easily let out dust or the like from inside, thereby permitting to assure a positive connection with the receptacle.




FIG.2

EP 0 883 084 A2

Description

BACKGROUND OF THE INVENTION

Field of the Invention:

The present invention relates to a memory card designed for reception in a memory card receptacle and into or from which information signal is to be written or read, and the memory card receptacle.

Description of Related Art:

A well-known memory card incorporating memory chips in which information signals are stored is provided with terminals which are to electrically be connected with an external system. The memory card is supplied with a voltage through the terminals and also delivers and receives information signal to and from the internal memory chips through the terminals.

Since the terminals for connection of the memory card to an external system are also electrically connected to the internal memory chips, they should be protected from being touched when the memory card is used. More particularly, if the terminals are directly touched, a static electricity will take place in them, which however is a rare case, and be carried from the terminals to the memory chips which thus will possibly be broken down. To avoid this, the terminals should be protected against easy access to them from outside to prevent such a breakdown due to a static electricity.

Also, the memory card of this type is featured by its transportability. So, it has been tried to design more compact memory cards for the convenience of portability. Thus, along with the more compact design of the memory card itself, its terminals have been designed thinner and arranged at reduced intervals.

Such thin, closely disposed terminals for connection to an external system will possibly be deformed and broken even if just lightly touched.

To prevent the terminals from being deformed or broken down, a memory card of this type has been proposed in which such terminals are buried inside in the memory card body and small holes communicating with the terminals are formed in the memory card body so that the terminals are exposed to outside only through the holes, or in which a concavity is formed in a forward end portion of the memory card body in the card inserting direction and terminals are disposed in the bottom of the concavity for protection of them.

However, the memory card in which the small holes are formed in the card body for the terminals to be exposed to outside is hard to disconnect from the receptacle if the holes are clogged with dust or the like. When the memory card is inserted into the receptacle with the holes left clogged with dust, no positive connection with the receptacle can be attained and also the terminals of the receptacle may possibly be deformed as the case

may be.

Further, the above memory card is apt to have a complicated structure and is manufactured with large costs. Therefore, the conventional memory card is not suitable for mass production.

Also, in the memory card having formed in the body thereof the concavity in which the terminals are disposed, the protection of the terminals cannot be protected to a satisfactory extent if the concavity is improperly shaped. If the concavity is not shaped for a satisfactory protection of the terminals, dust or the like is likely to heap or stay in the corners of the concavity and block the terminals of the memory card from secure connection with those of the receptacle.

Further a memory card has been proposed which is cut at one of the corners of a generally rectangular body thereof to prevent the memory card from being inserted incorrectly (in a wrong direction or posture) into a memory card receptacle. In this case, however, the memory card cannot be designed to have a variety of shapes by chamfering or rounding, for example, the other three corners.

SUMMARY OF THE INVENTION

The present invention has an object to overcome the above-mentioned drawbacks of the prior art by providing a memory card having a simple structure, adapted to positively protect terminals thereof and easily let out dust or the like from inside to attain a positive connection with a memory card receptacle, and designable to have a variety of corner shapes, and the memory card receptacle.

The above object can be accomplished by providing a memory card comprising a body, a concavity formed in the card body which is open at the top and forward end of the card body in the inserting direction of the latter, and terminals disposed in the concavity. The memory card has also a projection formed in at least a part of a space defined between two successive ones of the terminals disposed in the concavity to protect the terminals against access or touch from outside, and the inner wall of the concavity perpendicular to the inserting direction of the card body is inclined.

In this memory card, the projections are formed in the concavity to define sockets in each of which a terminal is disposed, whereby the terminals thus disposed in the concavity can be protected against access or touch from outside.

Since the concavity has the inclined inner wall, dust or the like, if any, can easily be let out from on the concavity wall when the memory card is inserted into a memory card receptacle.

The above object can also be accomplished by providing a memory card comprising a body, a concavity formed in the card body and open at the top and forward end, in the inserting direction, of the card body, and terminals disposed in the concavity. The memory card has

also a shutter member which opens and closes the concavity, and the inner wall of the concavity perpendicular to the inserting direction of the memory card is inclined.

When the memory card is not inserted into a memory card receptacle, the concavity is closed by the shutter member so that the terminals disposed inside the concavity cannot be accessed or touched from outside.

When the memory card is inserted into a memory card receptacle, dust or the like is removed to outside from the inclined wall of the concavity.

Also the above object can be accomplished by providing a memory card receptacle having a receiving concavity formed therein, a plurality of terminals disposed in the receiving concavity, and a plurality of projections provided ahead of the plurality of terminals correspondingly to the terminals of a memory card.

When the memory card is inserted into the receptacle, the projections go ahead of the receptacle terminals and slide on the memory card terminals to let out dust or the like from on the memory card receptacle.

BRIEF DESCRIPTION OF THE DRAWINGS

These objects and other objects, features and advantages of the present invention will become more apparent from the following detailed description of the preferred embodiments of the present invention when taken in conjunction with the accompanying drawings, of which:

FIG. 1A shows the construction of a first embodiment of the memory card according to the present invention;

FIG. 1B shows the construction of a second embodiment of the memory card of the present invention;

FIG. 2 is a perspective view of the memory card in FIG. 1A;

FIG. 3 is a bottom view of the memory card in FIG. 1A;

FIG. 4 is a perspective view of a third embodiment of the memory card according to the present invention;

FIG. 5A is a plan view of a fourth embodiment of the memory card according to the present invention, showing the essential portion thereof with a shutter member placed to close or cover the concavity;

FIG. 5B is a plan view of the memory card in FIG. 5A, showing the essential portion thereof with the shutter member placed to open the concavity;

FIG. 6A is a plan view of a fifth embodiment of the memory card according to the present invention, showing the essential portion thereof with a shutter member placed to close the concavity;

FIG. 6B is a plan view of the memory card in FIG. 6A, showing the essential portion thereof with the shutter member placed to open the concavity;

FIG. 7 is a sectional view of a first embodiment of

the memory card receptacle according to the present invention;

FIG. 8 is a front view of the memory card receptacle in FIG. 7;

FIG. 9 is a sectional view of the receptacle in FIG. 7 in which the memory card is received;

FIG. 10 is a sectional view of the receptacle in FIG. 7 in which another memory card of the present invention is received;

FIG. 11 is a plan view showing the essential portion of another memory card of the present invention;

FIG. 12 is a plan view showing an example of the shape of the memory card of the present invention;

FIG. 13 is a sectional view taken along the line X_1-X_2 of the memory card in FIG. 12;

FIG. 14 is a plan view showing an example of the construction of the receptacle of the present invention in which the memory card of the present invention is received;

FIG. 15 is a sectional view taken along the line Y_1-Y_2 in FIG. 14, showing the example of the construction of the receptacle of the present invention;

FIG. 16 is a plan view showing the memory card being correctly inserted in the receptacle;

FIG. 17 is a sectional view taken along the line Y_3-Y_4 in FIG. 16, showing the memory card being correctly inserted in the receptacle;

FIG. 18 is also a sectional view taken along the line Y_3-Y_4 in FIG. 16, showing the memory card correctly inserted in the receptacle;

FIG. 19 is a plan view showing the memory card being incorrectly inserted into the receptacle;

FIG. 20 is a sectional view taken along the line Y_5-Y_6 in FIG. 19, showing the memory card being incorrectly inserted into the receptacle;

FIG. 21 is a plan view showing an example of the shape of the memory card of the present invention;

FIG. 22 is a plan view showing an example of the shape of the memory card of the present invention;

FIG. 23 is a sectional view of the memory card, taken along the line Z_1-Z_2 in FIG. 22;

FIG. 24 is a plan view showing an example of the construction of the receptacle of the present invention in which the memory card of the present invention is inserted;

FIG. 25 is a sectional view of the receptacle, taken along the line W_1-W_2 in FIG. 24;

FIG. 26 is a sectional view showing the memory card being correctly inserted in the receptacle;

FIG. 27 is also a sectional view showing the memory card being correctly inserted in the receptacle;

FIG. 28 is a sectional view showing the memory card being incorrectly inserted into the receptacle;

FIG. 29 is a plan view showing an example of the shape of the memory card of the present invention;

FIG. 30 is a perspective view showing an example of the shape of the memory card of the present invention;

FIG. 31 is a view of the memory card from a point H in FIG. 30;

FIG. 32 is a view of the memory card from a point I in FIG. 30;

FIG. 33 is a sectional view of the memory card of the present invention inserted in the receptacle of the present invention; and

FIG. 34 is a sectional view of the memory card of the present invention inserted in the receptacle of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

A memory card according to the present invention is generally indicated with a reference 1.

It is a storage medium which is inserted, for use, into a receptacle of an external system such as a computer, audio equipment, etc. for read or write of information signal between the memory card and external system thus connected to the memory card. As shown in FIGS. 1A and 1B, the memory card 1 has a card body 2 incorporating a plurality of memory chips 3 such as flash memory, etc. to store information signal, and a controlling integrated circuit 4 (will be referred to as "controlling IC" hereafter) to write or read information signal into or from the memory chips 3.

Further, the memory card 1 has terminals 5 for connection to an external system as shown in FIG. 2. When the memory card 1 is inserted into a memory card receptacle, the terminals 4 are electrically connected to those of the memory card receptacle to supply a voltage to the controlling IC 4 and transfer information signal and various control signals between the memory card 1 and the external system. The memory card 1 adopts a serial interface and the terminals 5 provided count nine in number.

The card body 2 is a thin, flat, rectangular card made of a synthetic resin, for example. The memory card 1 of this embodiment adopts the serial interface and is designed to have nine terminals 5, and thus the card body 2 itself is small. As shown in FIG. 3, the card body 2 has a short side L_1 of which the length is smaller than a half of the length L_2 of the long side. For example, L_1 is 21.5 mm while L_2 is 50 mm, and the thickness of the card body 2 is 2.8 mm.

The card body 2 has an inadvertent erasure-preventive member 6 attached to the rear end thereof in the inserting direction of the card body 2 indicated with an arrow A in FIGS. 2 and 3. The inadvertent erasure-preventive member 6 is engaged on an inadvertent erasure-preventive switch (not illustrated) housed in the card body 2. Sliding the member 6 in a direction perpendicular to the inserting direction of the card body 2 will turn on/off the inadvertent erasure-preventive switch. Also, the card body 2 has formed on a lateral side thereof parallel to the inserting direction of the card body 2 an arcuate locking cut 7 which prevents the memory card 1

from being freely disengaged from the memory card receptacle once the memory card 1 is inserted in the receptacle. When the memory card 1 is inserted into the receptacle, a mating locking projection (not illustrated) provided on the receptacle is engaged in this locking cut 7 to prevent the memory card 1 from being freely disengaged from the receptacle.

At one lateral end in the inserting direction, the card body 2 is cut (at 8) obliquely with respect to the inserting direction of the card body 2. This cut 8 is formed to prevent the memory card 1 from being incorrectly inserted into the receptacle. Further, the card body 2 has formed a concavity 9 formed at the forward end, in the inserting direction, thereof.

The concavity 9 is formed open to the forward end of the card body 2 and extends longitudinally from the forward end, in the inserting direction, of the card body 2. The concavity 9 is deep a predetermined step from the top surface of the card body 2, and thus it is defined by three walls and a bottom 9b. One 9a of the walls of the concavity 9, inner and parallel to the forward open end, is inclined at a predetermined angle with respect to the bottom 9b.

Because of the forward open end and inclined inner wall 9a of the concavity 9 in the memory card 1, dust or the like in the concavity 9 can be easily let out when the memory card 1 is inserted into the receptacle.

In the concavity 9, there is disposed a plurality of terminals 5 for connection to corresponding terminals of the receptacle when the card body 2 is inserted into the receptacle. The terminals 5 are formed by punching a thin metal sheet or from a pattern of a printed wiring board. They are laid side by side on the bottom 9b of the concavity 9 in the inserting direction of the card body 2, and exposed to outside.

Since the memory card 1 of the present invention adopts the serial interface, the terminals 5 thus provided count nine in number. Namely, the nine terminals 5 disposed in the concavity 9 of the memory card 1 include a digital signal input/output terminal, a sync signal input terminal, a status signal input terminal, four voltage supply terminals, and two reserved terminals.

Further, there are formed between the terminals 5 inside the concavity 9 projections 10 serving to prevent an access or touch to the terminals 5 from outside. As shown in FIG. 2, for example, the projections 10 extend between the open forward end and the inner wall 9a of the concavity 9 parallel to the forward end, and count two in number to trisect the space in the concavity 9 in this case. Three terminals 5 are disposed in three sockets, respectively, defined by the projections 10 thus formed inside the concavity 9.

The projections 10 provided in the concavity 9 of the memory card 1 will prevent the user from inadvertently touching the terminals 5 when inserting the memory card 1 into the receptacle. The terminals 5 can be thus protected.

The central one of the terminals 5 disposed in the

three sockets defined by the projections 10 in the concavity 9 should desirably be connected to the ground potential.

Since the memory card 1 is connected at the central one of the terminals 5 to the ground potential, even when the user's finger is put into the concavity 9, it will touch the grounded one of the terminals 5 so that a static electricity, if any, caused by touching the terminals 5 with the finger will be connected to the earth and thus the memory chip 3 will not be damaged by the static electricity.

As shown in FIG. 4, the memory card 1 may have formed in the concavity 9 a corresponding number of the projections 10 to a desired number of the terminals 5, and have the terminals 5 disposed in the sockets, respectively, defined by the projections 10 in the concavity 9. The projections 10 thus formed for the terminals 5 will positively prevent the terminals 5 being accessed or touched from outside.

It should be noted that ten terminals 10 may be provided in the memory card 1 as shown in FIG. 1B. Three of these ten terminals 5 may be reserved ones. In the memory card 1 with such ten reserved terminals 5, the three reserved terminals 5 can be used as signal input or output terminals to permit a parallel interface using a total of four signal input or output terminals including the aforementioned digital signal input/output terminal.

The present invention has been described in the foregoing concerning an embodiment in which the projections 10 are formed in the concavity to prevent access or touch to the terminals 5. However, the memory card 1 according to the present invention may comprise a shutter member 11 which is moved to open or close the concavity 9. As shown in FIG. 5A, when the memory card 1 is not inserted in the receptacle, the shutter member 11 closes the concavity 9 to prevent access to the terminals 5. In this embodiment, the card body 2 has formed therein, over an axial distance substantially corresponding to the axial length of the concavity 9 from the inner wall 9a parallel to the forward end of the concavity 9, an indentation in which the shutter member 11 is slidable.

The shutter member 11 is a rectangular plate made of a synthetic resin, for example, and slightly larger in area than the top opening of the concavity 9, and it is installed at the forward end of the card body 2 to be movable in the inserting direction. While the memory card 1 is not inserted in the receptacle, the shutter member 11 is pressed to the forward end of the concavity 9 to cover the top opening of the concavity 9.

When the memory card 1 is inserted into the receptacle, it will abut at the forward end thereof on projections of the receptacle as will be further described later. As shown in FIG. 5B, as the memory card 1 is inserted, the shutter member 11 is pushed in by the projections against the force of a spring member 12 in the direction of arrow B, and moved into the above-mentioned indentation so that the concavity 9 will be open at the top

thereof.

When the memory card 1 is not inserted into the receptacle, the concavity 9 is covered by the shutter member 11, so that the terminals 5 are prevented from being accessed or touched from outside and thus protected.

In the memory card 1 according to this embodiment as well, the inner wall 9a parallel to the forward open end of the concavity 9 is inclined at a predetermined angle with respect to the bottom 9b. Also the shutter member 11 should desirably have an inclined forward end face.

The memory card 1 has thus the inclined inner wall 9a parallel to the forward open end of the concavity 9 and the inclined forward end face of the shutter member 11 so that when the memory card 1 is inserted into the receptacle, dust or the like in the concavity 9 can easily be let out from on the inclined wall and end face.

Also in this memory card 1, the projections 10 may be formed inside the concavity 9 to define sockets for the terminals 5 as shown in FIGS. 6A and 6B. Thus, the projections 10 can positively protect the terminals 5 by preventing touch to them even when the shutter member 11 is inadvertently opened with the memory card 1 not yet inserted into the receptacle. FIG. 6A shows the top opening of the concavity 9 being covered or closed by the shutter member 11 while FIG. 6B shows the shutter member 11 moved away from on the concavity 9 and thus the concavity 9 being open at the top thereof.

FIGS. 7 and 8 show a memory card receptacle, generally indicated with a reference 20, adapted to receive the memory card 1 having been described in the foregoing. When the memory card 1 constructed as in the above is used, it is inserted in the receptacle 20 as shown in FIGS. 7 and 8 to record or reproduce information signal into or from the memory card 1.

As shown, the memory card receptacle 20 has an opening 21 formed at the front end thereof, through which the memory card 1 is inserted into the receptacle 20. Also, the receptacle 20 has formed therein, in the inserting direction of the memory card 1 indicated with an arrow C in FIG. 7, a memory card receiving concavity 22 axially extending from the opening 21 to a depth in the receptacle 20 and in which the memory card 1 is received. There are disposed inside this memory card receiving concavity 22 tips of a plurality of terminals 23 electrically connected to an external system as shown in FIG. 7.

The terminals tips 23 are formed by punching a thin metal sheet, for example. The terminals 23 are supported with the bases thereof buried in the body of the receptacle 20 as shown. Therefore, the terminals 23 also work as leaf springs which depress the terminals 5 of the memory card 1 inserted in the receptacle 20. The terminals 23 have each a contact point 23a formed near the free ends thereof inside the receiving concavity 22 and which are put into contact with the terminals 5 of the memory card 1.

The terminals 23 of the receptacle 20 are equal in number to the terminals 5 of the memory card 1. In this embodiment of the receptacle 20, nine terminals 23 for the nine terminals 5 of the memory card 1 are provided in the receiving concavity 22.

Further, there are provided ahead of the terminals 23 disposed in the receiving concavity 22, that is to say, in positions corresponding to the forward end of the memory card 1 when inserted in the receptacle 20, projections 24 which will slide on the terminals 5 of the memory card 1 when the latter is inserted into the receptacle 20. The projections 24 are equal in number to the terminals 5 of the memory card 1 similarly to the terminals 23 of the receptacle 20. The projections 24 are provided ahead of the terminals 23. In this embodiment of the receptacle 20, nine projections 24 are thus provided for the nine terminals 5. When the memory card 1 is inserted into the receptacle 20, the projections 24 slide on the terminals 5 of the memory card 1 before they get into contact with the terminals 23 as shown in FIG. 9. The projections 24 will let out dust or the like from inside the concavity 9 of the memory card 1 over the inclined wall 9a of the concavity 9 of the memory card 1.

When the memory card 1 is inserted into the memory card receptacle 20, the projections 24 move ahead of the terminals 23 and slide on the terminals 5 of the memory card 1. After the projections 24 let out dust or the like from on the terminals 5, the terminals 23 get into contact with the terminals 5 of the memory card 1. Thus, the terminals 23 and 5 are electrically connected to one another in a positive manner.

In the receptacle 20, the plurality of projections 24 is provided ahead of the terminals 23 correspondingly to the terminals 5, respectively, of the memory card 1 in such a manner that the projections 24 can be well fitted into the sockets defined by the projections 10 inside the concavity 9 of the memory card 1 for the respective terminals 5. Thus, the receptacle 20 can suitably receive the memory card 1 of such a structure as well as the memory card 1 having the concavity 9 of which the space is similarly trisected by the projections 10.

Further, the receptacle 20 can well receive the memory card 1 having the concavity 9 of which the top opening can be covered by the shutter member 11 for protection of the terminals 5. In this example, when the memory card 1 having the shutter member 11 is inserted into the receptacle 20, the projections 24 abut at the front end faces thereof on the forward end of the shutter member 11 which will thus be moved open as the memory card 1 is further inserted into the receptacle 20, as seen from FIG. 10.

Also it is of course that the receptacle 20 can receive a memory card having only the concavity 9 formed at the forward end, in the inserting direction, of the card body 2, and the terminals 5 disposed in the concavity 9, as shown in FIG. 11, with the projections 10 and shutter member 11 not provided.

The memory card receptacle 20 is versatile as having been described in the above, namely, it can be universally applied without being restricted by the shape of the memory card 1.

It should now be noted that the memory card according to the present invention may also be constructed as will be discussed below.

FIG. 12 is a plan view of an example of the memory card, and FIG. 13 is a sectional view taken along the line X_1-X_2 of the memory card in FIG. 12.

The memory card is generally indicated with a reference 100. It has a generally rectangular flat shape having four corners 101a, 101b, 101c and 102. Of these four corners, one (101a) of the corners at the forward end, in the inserting direction, of the memory card 100 indicated with the arrow D, and both the corners 101b and 101c at the rear end, in the inserting direction of, the memory card 100 indicated with the arrow D, are chamfered much more than the remaining corner, or the latter is not chamfered. Namely, the memory card 100 is so shaped that it can be judged based on the position of the corner 102 whether the memory card 100 being inserted into the receptacle is positioned correctly or incorrectly, whereby the memory card 100 can be prevented from incorrectly being inserted into the receptacle.

As mentioned above, the remaining corner 102 at the forward end, in the inserting direction, of the memory card 100 indicated with the arrow D is not chamfered while the other three corners 101a, 101b and 101c are chamfered to have an arcuate form, for example. Furthermore, the corner 101a is rounded much more than the other two corners 101b and 101c as shown in FIG. 12.

When used for information recording or reproduction, the memory card 100 is inserted into a receptacle 103 as shown in FIGS. 14 and 15. FIG. 14 is a plan view of an example of the receptacle 103, and FIG. 15 is a sectional view taken along the line Y_1-Y_2 of the receptacle 103 in FIG. 14. Although FIG. 14 is a plan view, hatching is made somewhere therein for better understanding of the relation between the members of the receptacle 103.

The receptacle 103 has formed at the forward end thereof an opening 104 through which the memory card 100 is to be inserted, formed therein a receiving concavity 105 extending from the opening 104 along the inserting direction of the memory card 100 indicated with an arrow E, and provided at the innermost portion of the opening 104 an incorrect insertion-preventive member 106 extending in the inserting direction of the memory card 100 indicated with the arrow E.

The incorrect insertion-preventive member 106 has at the opening 104 of the receptacle 103 a front end face 107 extending generally perpendicular to the inserting direction of the memory card 100, and a projection 108 formed at one of the lateral ends of the front end face 107. The projection 108 has an oblique surface

109 which becomes thinner and narrower as it goes from the front end face 107 toward the opening 104. The oblique surface 109 detects the corner 102 of the memory card 100.

Further the incorrect insertion-preventive member 106 is pivoted and forced clockwise in the plane of FIG. 15 under the action of a coil spring 110. When the receptacle 103 is not used, the member 106 closes the opening 104 to block dust or the like from coming into the receptacle 103.

FIGS. 16, 17 and 18 show the memory card 100 correctly inserted in the receptacle 103. As the memory card 100 is inserted from the opening 104 in the direction of arrow E, it will abut at the corner 102 thereof on the projection 108 formed on the incorrect insertion-preventive member 106 as shown in FIG. 16. Then the upper end of the corner 102 slides on the oblique surface 109 of the projection 108 as shown in FIG. 17 and urges up the incorrect insertion-preventive member 106. Eventually the corner 102 will allow the incorrect insertion-preventive member 106 to escape as shown in FIG. 18 and thus the memory card 100 is allowed to go into place in the receptacle 103.

FIGS. 19 and 20 show the memory card 100 being inserted in a wrong direction into the receptacle 103. As the memory card 100 is inserted in the direction of arrow E, the rounded corner 101a will not abut on the projection 108 of the incorrect insertion-preventive member 106 but at the forward end, in the inserting direction, thereof on the front end face 107 of the incorrect insertion-preventive member 106. Since the front end face 107 of the member 106 is formed generally perpendicular to the inserting direction of the memory card 100 indicated with the arrow E, the forward end of the memory card 100 will be caught by the projection 108 and thus cannot urge up the incorrect insertion-preventive member 106. Therefore, if the memory card 100 is incorrectly inserted into the receptacle 103, the corner 101a will not allow the incorrect insertion-preventive member 106 to escape, so that the memory card 100 cannot be inserted deep into place in the receptacle 103.

FIGS. 19 and 20 show an example in which the memory card 100 is inserted upside down in the receptacle 103. Also in this case, the corners 101b and 101c will not allow the incorrect insertion-preventive member 106 to escape, so that the memory card 100 cannot be inserted deep into place in the receptacle 103. Therefore, it is only when the memory card 100 is inserted correctly that the memory card 100 can be inserted deep into place in the receptacle 103. Thus, the memory card 100 can be prevented from being incorrectly inserted into the receptacle 103.

For the purpose of preventing an incorrect insertion of the memory card 100, the corners 101a, 101b and 101c have only to be formed not to abut on the projection 108 of the incorrect insertion-preventive member 106, and thus may be shaped to have any flat form. For

example, the corners may be chamfered in different sizes as well as in various shapes such as arcuate, linear or the like as shown in FIG. 21. Such variations in chamfered size and shape of the corners will also give a variation to the memory card design.

Also it should be noted that the memory card according to the present invention may be constructed as will be discussed below:

FIG. 22 shows, in the form of a plan view, an example of the memory card, and FIG. 23 is a sectional view taken along the line Z₁-Z₂ of the memory card shown in FIG. 22.

This memory card 120 is generally rectangular in shape, and cut at 121 at the bottom edge of the forward end thereof in the inserting direction indicated with an arrow F as will be seen from FIG. 23. The cut 121 extends over the entire forward-end short side of the memory card 120, and provides an oblique flat end face.

For preventing incorrect insertion of the memory card 120, it is judged based on the position of this cut 121 whether the memory card 120 is inserted correctly or incorrectly, as will be discussed below.

For information recording or reproduction, the memory card 120 is inserted into place in a receptacle 122 as shown in FIGS. 24 and 25. FIG. 24 is a plan view of an example of the construction of the receptacle 122, and FIG. 25 is a sectional view taken along the line W₁-W₂ of the receptacle 122 shown in FIG. 24. The receptacle 122 has formed at the forward end thereof an opening 123 through which the memory card 120 is to be inserted, formed therein a receiving concavity 124 extending from the opening 123 in the inserting direction of the memory card 120 indicated with an arrow G, and provided at the innermost portion of the opening 123 an incorrect insertion-preventive member 125 extending in the inserting direction of the memory card 120 indicated with the arrow G.

As shown in FIG. 25, the incorrect insertion-preventive member 125 has a blocking plate 127 having a first face 126 generally perpendicular to the inserting direction of the memory card 120 indicated with the arrow G, and a projection 129 provided at the upper end of the blocking plate 127 on the side of the opening 123 and which has a second face 128 generally parallel to the inserting direction of the memory card 120.

Further the incorrect insertion-preventive member 125 is pivoted and forced clockwise in the plane of FIG. 25 under the action of a coil spring 130. When the receptacle 122 is not used, the member 125 closes the opening 123 to block dust or the like from coming into the receptacle 122.

As the memory card 120 is inserted into the receptacle 122, the incorrect insertion-preventive member 125 is rotated about 90 deg. counterclockwise (in the plane of Figure) against the action of the coil spring 130 and the first face 126 will be generally parallel to the inserting direction of the memory card 120.

When the memory card 120 is correctly inserted

into the receptacle 122, that is to say, when the cut 121 formed at the bottom edge of the forward end of the memory card 120 is positioned down, the forward end of the memory card 120 will slide at the oblique face of the cut 121 onto the projection 129 to depress the incorrect insertion-preventive member 125, as shown in FIG. 26. Thus, the cut 121 will allow the incorrect insertion-preventive member 106 to escape as shown in FIG. 27 and thus the memory card 120 is allowed to go deep into place in the receptacle 122.

When the memory card 120 is inserted in a wrong direction into the receptacle 122, that is, when the cut 121 is not positioned down as shown in FIG. 28, the memory card 120 will abut at the forward end thereof onto the second face 128 of the projection 129. Since the second face 128 is generally perpendicular to the inserting direction of the memory card 120 indicated with the arrow G, the forward end of the memory card 120 is caught by the projection 129 so that it cannot depress the incorrect insertion-preventive member 125. Therefore, when the memory card 120 is inserted in a wrong direction, the incorrect insertion-preventive member 125 cannot be allowed to escape to insert the memory card 120 deep into place in the receptacle 122.

FIG. 28 shows the memory card 120 being inserted upside down into the receptacle 122. Also when the memory card 120 is inserted in a reverse direction, the incorrect insertion-preventive member 125 cannot be allowed to escape to insert the memory card 120 deep into place in the receptacle 122. Therefore it is only when the memory card 120 is inserted correctly that it can be inserted deep into place in the receptacle 122. Thus, it is possible to prevent incorrect insertion of the memory card 120.

Since it is judged based on the shape in the direction of the width of the memory card 120 whether the memory card 120 is inserted correctly or incorrectly, the cut 121 has only to be formed to a size over which the projection 129 can be slid to depress the incorrect insertion-preventive member 125. Therefore, for the purpose of preventing an incorrect insertion of the memory card 120, the corners thereof has only to be shaped to have any flat form. For example, the memory card 120 may be chamfered at the corners thereof in different sizes as well as in various shapes such as arcuate, linear or the like, as shown in FIG. 29. Such variations in chamfered size and shape of the corners will also give a variation to the memory card design.

In addition to the above-mentioned structure designed for insertion into the receptacle, the memory card according to the present invention may be designed for fitting onto the top of the receptacle

FIG. 30 shows an example of the memory card of such design. In this case, the memory card is generally indicated with a reference 140. FIG. 31 is a view of the memory card 140 from a direction H in FIG. 30, and FIG. 32 is a view of the memory card 140 from a direction I in FIG. 30. The memory card 140 has a generally

rectangular flat shape. Also the memory card 140 has recesses 143a and 143b formed at end portions, respectively, of a first longitudinal side 141 thereof and also recesses 143c and 143d formed at end portions, respectively, of a second longitudinal side 142 parallel to the first longitudinal side, as shown in FIG. 31.

The memory card 140 can be fitted into a receptacle 144 using the recesses 143a to 143d thereof as will be described below.

As shown in FIG. 33, the receptacle 144 has formed on the top thereof a concavity 145, for example, in which the memory card 140 is to be fitted. The concavity 145 is open at the top thereof, and projections 146 are formed on side walls, respectively, of the concavity 145. For example, the memory card 140 can be fitted to the receptacle 144 with the projections 146 of the receptacle 144 engaged in the recesses 143 (143a to 143d) of the memory card 140, as shown in FIG. 34.

The memory card 140 can be directly set in a recording/reproducing apparatus. Also, the memory card 140 may be fitted in an adapter having a shape of a flexible disk, PC card or the like, for example, and then the adapter in which the memory card 140 is fitted be set in the recording/reproducing apparatus.

In this case, since the memory card is fitted in a receptacle and then set in the recording/reproducing apparatus, the top cover of the receptacle is unnecessary and the receptacle can be designed thinner than a one which is to receive the memory card therein so that the receptacle can be designed more compact. Also, the above-mentioned adapter destined to have the memory card fitted therein for setting into a recording/reproducing apparatus can be designed to have a reduced thickness.

Claims

1. A memory card, comprising:

a card body incorporating memory chips;
a concavity open at the top and forward end, in the inserting direction, of the card body; and
a plurality of terminals disposed side by side in the concavity in the inserting direction of the card body; and
a projection being formed in at least a part of a space defined between two successive terminals disposed in the concavity to protect the terminals against touch from outside;
the inner wall of the concavity perpendicular to the inserting direction of the card body being inclined.

2. The memory card as set forth in Claim 1, wherein the projections are formed between two successive ones of all the terminals.

3. The memory card as set forth in Claim 1, wherein a

serial interface is adopted.

4. The memory card as set forth in Claim 1, wherein the card body is shaped flat and generally rectangular in the inserting direction thereof and the length of the short side thereof is less than a half of that of the long side. 5
5. The memory card as set forth in Claim 1, wherein a cut for preventing disengagement of the card body is formed on one of the lateral sides parallel to the inserting direction of the card body. 10
6. The memory card as set forth in Claim 1 wherein a cut for preventing disengagement of the card body is formed at one lateral corner of the forward end, in the inserting direction, of the card body. 15
7. The memory card as set forth in Claim 1, wherein a cut for preventing incorrect insertion of the card body is formed at the forward end, in the inserting direction, of the card body, the cut being made in the direction of the card body thickness. 20
8. The memory card as set forth in Claim 1, wherein one of the corners of the front end, in the inserting direction, of the card body and both corners of the rear end, in the inserting direction, of the card body are much more chamfered than the other corner at the forward end, in the inserting direction, of the card body. 25 30
9. The memory card as set forth in Claim 1, wherein the card body has formed on the lateral side thereof recesses for fitting. 35
10. A memory card comprising:
 - a card body incorporating memory chips;
 - a concavity open at the top and extending longitudinally of the card from the forward end of the card body; and
 - a plurality of terminals disposed side by side in the concavity in the inserting direction of the card body; and
 - a shutter member movable to open and close the concavity; and
 - the inner wall of the concavity perpendicular to the inserting direction of the memory card being inclined. 40 45
11. The memory card as set forth in Claim 10, wherein a serial interface is adopted.
12. The memory card as set forth in Claim 10, wherein the card body is shaped flat and generally rectangular in the inserting direction thereof and the length of the short side thereof is less than a half of 55

that of the long side.

13. The memory card as set forth in Claim 10, wherein a cut for preventing disengagement of the card body is formed on one of the lateral sides parallel to the inserting direction of the card body.
14. The memory card as set forth in Claim 10, wherein a cut for preventing disengagement of the card body is formed at one lateral end of the forward end face, in the inserting direction, of the card body.
15. The memory card as set forth in Claim 10, wherein a cut for preventing incorrect insertion of the card body is formed at the forward end, in the inserting direction, of the card body, the cut being made in the direction of the card body thickness.
16. The memory card as set forth in Claim 10, wherein one of the corners of the front end, in the inserting direction, of the card body and both corners of the rear end, in the inserting direction, of the card body are much more chamfered than the other corner at the forward end, in the inserting direction, of the card body.
17. The memory card as set forth in Claim 10, wherein the card body has formed on the lateral side thereof recesses for fitting.
18. A memory card receptacle comprising:
 - a receiving concavity open at the front end of the receptacle and in which a memory card introduced from the opening is set;
 - a plurality of terminals having tips disposed inside the receiving concavity and which are to be connected to terminals of the memory card; and
 - a plurality of projections provided ahead of the plurality of terminals and which slide on the terminals of the memory card when the latter is inserted into the receptacle;
 - the sliding projections corresponding in number to the memory card terminals.
19. The receptacle as set forth in Claim 18, wherein a serial interface is adopted.
20. A memory card receptacle comprising:
 - a receiving concavity in which a memory card introduced from an opening formed at the front end of the receptacle is set; and
 - an incorrect insertion-preventive member provided deep in the opening in the inserting direction of the memory card;
 - the incorrect insertion-preventive member hav-

ing a front face generally perpendicular to the inserting direction of the memory card and a projection formed on one lateral end of the front face;

the projection having an oblique face formed gradually reduced in thickness and width as it goes from the front face of the incorrect insertion-preventive member toward the opening; the incorrect insertion-preventive member being pivoted and depressed under the action of a coil spring downward from the inserting direction of the memory card in the receiving concavity.

21. The receptacle as set forth in Claim 20, wherein a serial interface is adopted.

22. A memory card comprising:

a receiving concavity in which a memory card introduced from an opening formed at the front end of the concavity is set; and an incorrect insertion-preventive member provided deep in the opening in the inserting direction of the memory card; the incorrect insertion-preventive member comprising a blocking plate having a first face generally perpendicular to the inserting direction of the memory card and a projection formed at the top end of the blocking plate and on the opening side and which has a second face generally parallel to the inserting direction of the memory card; and the incorrect insertion-preventive member being pivoted to depress the projection under the action of a coil spring toward the opening.

23. The receptacle as set forth in Claim 22, wherein a serial interface is adopted.

24. A memory card receptacle comprising:

a receiving concavity in which a memory card introduced from an opening formed on the top of the concavity is set; and projections formed on the lateral walls of the receiving concavity for engagement into recesses formed in the lateral sides of the memory card.

25. The receptacle as set forth in Claim 24, wherein a serial interface is adopted.

26. The memory card as set forth in Claim 1, provided therein nine terminals for connection to an external system.

27. The memory card as set forth in Claim 10, provided

therein nine terminals for connection to outside.

28. The memory card as set forth in Claim 1, provided therein ten terminals for connection to outside.

29. The memory card as set forth in Claim 10, provided therein nine terminals for connection to outside.

30. The memory card as set forth in Claim 4, wherein the short side thereof is 21.5 mm long while the long side is 50 mm long.

31. The memory card as set forth in Claim 12, wherein the short side thereof is 21.5 mm long while the long side is 50 mm long.

32. The memory card as set forth in Claim 1, wherein the card body is shaped flat and rectangular in the inserting direction, the short side thereof is 21.5 mm long, the long side is 50 mm long and the thickness is 2.8 mm.

33. The memory card as set forth in Claim 10, wherein the card body is shaped flat and rectangular in the inserting direction, the short side thereof is 21.5 mm long, the long side is 50 mm long and the thickness is 2.8 mm.




FIG.1A




FIG.1B




FIG.2




FIG. 3




FIG. 4




FIG. 5A




FIG. 5B




FIG. 6A




FIG. 6B




FIG. 7




FIG. 8




FIG.9




FIG.10




FIG. 11




FIG. 12



FIG.13




FIG.14




FIG.15




FIG.16




FIG.17




FIG.18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG.27




FIG.28




FIG.29




FIG.30




FIG. 31




FIG. 32




FIG. 33




FIG.34



(11) **EP 0 883 084 A3**

(12) **EUROPEAN PATENT APPLICATION**

(88) Date of publication A3:
 12.09.2001 Bulletin 2001/37

(51) Int Cl.7: G06K 19/077, G06K 7/00

(43) Date of publication A2:
 09.12.1998 Bulletin 1998/50

(21) Application number: 98110232.0

(22) Date of filing: 04.06.1998

(84) Designated Contracting States:
 AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
 MC NL PT SE
 Designated Extension States:
 AL LT LV MK RO SI

- Kobayashi, Toshiharu
 Shinagawa-ku, Tokyo (JP)
- Okaue, Takumi
 Shinagawa-ku, Tokyo (JP)
- Sassa, Akira
 Shinagawa-ku, Tokyo (JP)

(30) Priority: 04.06.1997 JP 14691497
 30.09.1997 JP 26718197

(74) Representative: Körber, Wolfhart, Dr. rer.nat. et al
 Patentanwälte
 Mitscherlich & Partner,
 Sonnenstrasse 33
 80331 München (DE)

(71) Applicant: SONY CORPORATION
 Tokyo (JP)

(72) Inventors:
 • Kondo, Yoshio
 Shinagawa-ku, Tokyo (JP)

(54) **Memory card, and receptacle for same**

(57) A memory card is disclosed which has a card body (2) having a concavity (9) formed at the forward end thereof in the inserting direction and in which terminals (5) are disposed and projections (10) are formed between the terminals (5) to prevent the terminals (5) from being touched or accessed from outside. A receptacle for the memory card is also disclosed. The memory card has a simple structure designed to positively protect the terminals and easily let out dust or the like from inside, thereby permitting to assure a positive connection with the receptacle.




FIG.2

EP 0 883 084 A3

EP 0 883 084 A3

European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 98 11 0232

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X	US 5 157 244 A (RITCHIE LEON T ET AL) 20 October 1992 (1992-10-20) * column 3, line 22 - line 27 *	18	G06K19/077 G06K7/00
A	* column 5, line 48 - column 7, line 13 * * column 8, line 35 - line 52 * * figures 1-8 *	1,10	
X	EP 0 263 746 A (FRANCELCO SA) 13 April 1988 (1988-04-13) * the whole document *	20-23	
A		1,10,18	
X	EP 0 702 325 A (NACIONAL MONEDA TIMBRE) 20 March 1996 (1996-03-20) * the whole document *	24,25	
X	WO 95 11135 A (OKI ELECTRIC IND CO LTD ;ATSUMI SHIRO (JP)) 27 April 1995 (1995-04-27) & US 5 736 781 A 7 April 1998 (1998-04-07) * column 1, line 59 - column 2, line 17 * * column 5, line 42 - column 9, line 41 * * figures 1,8-10,13 *	24,25	
A	PATENT ABSTRACTS OF JAPAN vol. 009, no. 329 (P-416), 24 December 1985 (1985-12-24) & JP 60 153583 A (MITSUBISHI JUSHI KK), 13 August 1985 (1985-08-13) * abstract *	1,10,18	TECHNICAL FIELDS SEARCHED (Int.Cl.6) G06K
A	US 4 733 061 A (HEGI PAUL) 22 March 1988 (1988-03-22) * column 3, line 54 - line 56 * * figure 4 *	1,10,18	
A	US 4 511 796 A (AIGO SEIICHIRO) 16 April 1985 (1985-04-16) * the whole document *	24,25	
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 23 July 2001	Examiner Rydman, J
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosures P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

EPO FORM 1503 (Rev. 01/91)



European Patent
Office

Application Number
EP 98 11 0232

CLAIMS INCURRING FEES

The present European patent application comprised at the time of filing more than ten claims.

- ☐ Only part of the claims have been paid within the prescribed time limit. The present European search report has been drawn up for the first ten claims and for those claims for which claims fees have been paid, namely claim(s):
- ☐ No claims fees have been paid within the prescribed time limit. The present European search report has been drawn up for the first ten claims.

LACK OF UNITY OF INVENTION

The Search Division considers that the present European patent application does not comply with the requirements of unity of invention and relates to several inventions or groups of inventions, namely:

see sheet B

- ☒ All further search fees have been paid within the fixed time limit. The present European search report has been drawn up for all claims.
- ☐ As all searchable claims could be searched without effort justifying an additional fee, the Search Division did not invite payment of any additional fee.
- ☐ Only part of the further search fees have been paid within the fixed time limit. The present European search report has been drawn up for those parts of the European patent application which relate to the inventions in respect of which search fees have been paid, namely claims:
- ☐ None of the further search fees have been paid within the fixed time limit. The present European search report has been drawn up for those parts of the European patent application which relate to the invention first mentioned in the claims, namely claims:



European Patent
Office

LACK OF UNITY OF INVENTION
SHEET B

Application Number
EP 98 11 0232

The Search Division considers that the present European patent application does not comply with the requirements of unity of invention and relates to several inventions or groups of inventions, namely:

1. Claims: 1-19, 26-33

A memory card comprising a concavity open at the top and forward end of the the card body and a plurality of terminals disposed side by side in the cavity, the inner wall of the concavity perpendicular to the inserting direction of the card body being inclined.

A memory card receptacle with a concavity for receiving a memory card, a plurality of terminals to be connected to the terminals of the memory card and a plurality of projections provided ahead of the terminals, which slide on the terminals when the memory card is inserted into the receptacle.

2. Claims: 20-23

A memory card receptacle comprising an incorrect insertion-preventive member provided deep in the opening of the receptacle, the incorrect insertion-preventive member being pivoted.

3. Claims: 24, 25

A memory card receptacle comprising a receiving concavity in which a memory card is introduced from an opening formed on the top of the concavity and projections formed on the lateral walls of the receiving concavity for engagement into recesses formed in the lateral sides of the memory card.

EP 0 883 084 A3

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 98 11 0232

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

23-07-2001

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5157244	A	20-10-1992	US 5321247 A	14-06-1994
EP 0263746	A	13-04-1988	FR 2604804 A	08-04-1988
			DE 3778110 A	14-05-1992
EP 0702325	A	20-03-1996	ES 2102317 A	16-07-1997
			AU 695335 B	13-08-1998
			AU 3069995 A	04-04-1996
			CA 2158530 A	20-03-1996
			FI 954418 A	20-03-1996
			NO 953678 A	20-03-1996
			NZ 280036 A	24-06-1997
			ZA 9507890 A	29-04-1996
WO 9511135	A	27-04-1995	US 5736781 A	07-04-1998
JP 60153583	A	13-08-1985	NONE	
US 4733061	A	22-03-1988	CH 661808 A	14-08-1987
			DE 189039 T	27-11-1986
			EP 0189039 A	30-07-1986
US 4511796	A	16-04-1985	NONE	

EPO FORM P443

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.